

# Introduction of Nanomaterials

---

## Introduction

A material with

- any external dimension in the nanoscale (size range from approximately **1–100 nm**).
- having internal structure or surface structure in the nanoscale.

At nanoscale, materials exhibit very unusual and very interesting properties. Examples: Graphene has very high young's modulus and very high carrier mobility.

## Nano-object

An object with any external dimension is in the nanoscale.

Examples: carbon nanotube, bucky ball.

## Nano-structured material

A material where its internal or surface structure is in the nanoscale.

Examples: **TiO<sub>2</sub>** nanotube films.

## Nano in nature

- Lotus leaves being super-hydrophobic
- Gecko adhesive system

## Nano-science

Study of structures and materials on the nanoscale.

## Nanotechnology

Development of materials and devices by exploiting the characteristics of particles on the nanoscale.

## Applications

- Nanoscale transistors
  - Higher-performance
  - Improved energy efficiency
- Magnetic data storage
  - High data density and data capacity
  - Ultra compact
- Nano-medicine and drug delivery
- Energy storage

## Preparation of nanomaterials

### Top-down approach

Nanoscale dimensions are created using larger components, by externally controlled devices.

Examples: Lithography, Etching techniques.

### Photolithography

Can be used to create nanoscale patterns in thin films or bulk substrates.

The steps:

1. Coat **Si** wafer with a photosensitive material.  
A material which changes its properties when exposed to electromagnetic radiation
2. Add a mask and use an EM radiation.
3. Developer solution removes either reacted or unreacted material.
4. The silicon wafer is etched to transfer the pattern onto silicon wafer.
5. Photosensitive material is removed.

### Bottom-up approach

Molecular components arrange themselves into more complex nano materials/objects.

Examples: Molecular self-assembly, Chemical vapour deposition

# Graphene

Carbons arranged to a hexagonal network. 2D crystal based. Has 3 fold symmetry. Single sheet of graphite.

## Unit Cell

- A rhombus with  $120^\circ$ .
- Lattice parameter (side length of a unit cell)  $a = 2d \cos 30^\circ$  where  $d$  is the  $\text{C} - \text{C}$  bond length.
- 2 atoms per unit cell.

### Note

Single layer of graphene was discovered using scotch tape method and the discovery won a Nobel prize in 2010.

## Synthesis

- Top-down approaches
  - Exfoliation (eg: Scotch tape method)
- Bottom-up approaches
  - Chemical vapor deposition

## Properties

- Band gap is **0**
- High tensile strength (  $\sim 1100 \text{ GPa}$  )
- High young's modulus (  $\sim 1 \text{ TPa}$  )
- High charge carrier mobility ( **2** )
- Highly transparent ( **97** )

## Carbon Nanotubes

A rolled up sheet of graphene.


# Classifications

## Based on structure

1. Single wall carbon nanotubes (SWNT)
2. Multi-walled carbon nanotubes (MWNT)  
Similar to graphite but rolled up as a set of sheets.

## Based on Chirality

Chirality means the way that graphene sheet is oriented with respect to the axis of carbon nanotube.




## Achiral

Have mirror planes. Has 2 types.


1. Armchair
2. Zigzag

## Armchair



Circumference has a repeating armchair structure.

## Zigzag



Circumference has a repeating zigzag structure.


## Chiral

No mirror planes. Definition for the chiral type is later explained.

## Definitions

### Equivalent Atoms

Equivalent atoms means the atoms having the same surrounding.



In graphene, next-near neighbours are equivalent atoms.

When a graphene sheet is rolled to create a CNT, only equivalent atoms can be connected.

### Primitive Vectors

Vectors used to describe a unit cell.

For graphene, any 2 adjacent sides of the unit cell can be used as the primitive vectors.

### Lattice Vectors

Any vector connecting 2 equivalent atoms. A lattice vector can be expressed in terms of primitive vectors.

### Chiral Vector

The vector that constructs the circumference of a CNT. Also called as Circumferential vector.

## **(n,m) notation**

If the chiral vector can be expressed as  $na_1 + ma_2$  where  $a_1, a_2$  are the primitive vectors, then the notation for the nanotube is  $(n, m)$

- $n = 0 \vee m = 0$  : zigzag tube
- $n = m$  : armchair tube
- Otherwise: chiral tube

## **Chiral Angle**

Angle between the chiral vector and nearest zigzag angle.

For a  $(n, m)$  tube where  $n > 0$  and  $n \geq m \geq 0$ :

$$\theta = \tan^{-1} \left( \frac{\sqrt{3}m}{2n + m} \right)$$

- $\theta = 30^\circ$  : armchair tube
- $\theta = 0^\circ$  : zigzag tube
- $0^\circ < \theta < 30^\circ$  : chiral tube

## **Chiral Vector Length**

For a  $(n, m)$  tube, the chiral vector's length is given by:

$$|\text{CH}| = a\sqrt{n^2 + m^2 + nm}$$

Here  $a$  is the bond length of C-C.

## **Diameter of CNT**

The diameter can be expressed by:

$$D = \frac{|\text{CH}|}{\pi} = \frac{a}{\pi} \sqrt{n^2 + m^2 + nm}$$

## Properties

- Mechanical properties
  - High young's modulus: depends on tube diameter, multi-walled or single-walled but not tube chirality.
  - Sustains higher strain
- Electrical properties
  - Depends on chirality and size
  - Exhibits superconductivity at **20K**
  - Band structure changes with chirality
- Thermal properties
  - Conducts thermal energy only in the axial direction; radial direction is insulating

## Chirality dependent electrical properties

For a  $(n, m)$  tube:

- If  $n = m$  , its armchair typed and is metallic (good conductors)
- If  $n - m$  is a integer multiple of **3** : small band gap semiconductors
- Else: large band gap semiconductors

Band gap decreases as the radius of the diameter increases.

## Applications

- Conductive or reinforced plastic
- CNT based transistors
- Molecular electronics
- Energy storage devices
- Biomedical applications